

Kenevo SL Comp

Frame

FACT 11m full carbon, 29", full internal cable routing, 148mm spacing, fully sealed cartridge bearings, 170mm rear travel, geo adjust head tube, geo adjust horst pivot

Rear Shock

FOX FLOAT X Performance, LSR, 2-position lever, 62.5x230mm

Fork

FOX FLOAT 36 RHYTHM 29, GRIP damper, 44mm offset, 2-position sweep adjust, 15x110mm, 1.5" tapered steerer, 170mm travel

Stem

Alloy Trail Stem, 35mm bar bore

Tape

Specialized Trail Grips

Handlebars

Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 30mm rise, 800mm width

Saddle

Bridge Comp, Hollow Cr-mo rails, 155/143mm

Front Brake

SRAM Code R, 4-piston caliper, hydraulic disc, 220mm

Rear Brake

SRAM Code R, 4-piston caliper, hydraulic disc, 200mm

Rear Derailleur

SRAM GX Eagle, 12-speed

Shift Levers

SRAM GX Eagle, 12-speed

Cassette

SRAM XG-1275, 12-speed, 10-52t

Chain

SRAM NX Eagle, 12-speed

Crankset

Praxis, forged M30, custom offset

Chainrings

SRAM X-Sync Eagle, 94 BCD, 32T, alloy

Rims

Specialized 29, hookless alloy, 30mm inner width, tubeless ready

Front Hub

Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h

Rear Hub

Alloy, sealed cartridge bearings, 148mmx12mm thru-axle, 28h

Front Tire

Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"

Spokes

DT Swiss Industry

Rear Tire

Butcher, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, 29x2.3"

Inner Tubes

Standard, Presta valve

SeatPost

X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9mm, S2: 125mm, S3/S4: 150mm, S5: 170mm

Seat Binder

Alloy, 38.6mm

Motor

Specialized SL 1.1, custom lightweight motor

UI/Remote

Specialized MasterMind TCU, ANT+/Bluetooth®, w/Handlebar remote

Battery

Specialized SL1-320, fully integrated, 320Wh

Charger

Custom charger, 48V System w/ SL system charger plug

Wiring Harness

Custom Specialized wiring harness

SWAT

SWAT CC, integrated tool and chain tool with spare link in steerer tube